

DATA SHEET

FLEXIBLE CAMERA PROBE Ø 9 MM

0,80 Meter for RUNPOCAM RC 2

Item no.: 20481



DATA

ITEM NO.	20481
WEIGHT KG	0,19 kg
DIMENSION	L 340 mm B 270 mm H 85 mm
CAMERA PROBE	300.000 Pixel (720x576)
ILLUMINATION	4 x LED (dimnable)
PROTECTION CLASS	IP 67
FIELD OF VIEW	64 °
DIAMETER	9 mm
EAN-CODE	9120045475081

ADVANTAGES

- ✓ Flexible gooseneck for individual viewing angle adjustment
- ✓ Protection class IP67
- ✓ Suitable for RUNPOCAM RC 2
- ✓ Angle of view 64°

DESCRIPTION

Camera attachment flexible Ø 9 mm for RUNPOCAM
Application: optimal for short distances with flexible gooseneck. For cavity wall, plant, machinery, engine, ventilation, control or inspection. Hidden cavities, narrow angles, shafts, channels, small lead-throughs and many other possible applications.

Technical data: length: 0.8 m

Camera head: Ø 9 mm, resolution - 300,000 pixels (720 x 576), protection class - IP67, angle of view - 64 degrees, 4 x LED adjustable in 6 steps, auto focus.

Application video: a short, very informative application video can be viewed by scanning the QR code (top left) or on www.runpotec.com.

Scope of delivery: camera head Ø 9 mm flexible - 0.80 metre for RUNPOCAM RC 2

INFORMATION

Use with:

RUNPOCAM RC2

Length: 10 m | 30 m | 50 m

Item no: 10139 | 10140 | 10141

