

DATASHEET

RUNPO 5 + PROFI SET 4,5 mm

Profi cable pullingsystem + Fiberglass rod

Item no.: 11120



VIDEO

RUNPO 5

Click here Video

VIDEO

Fiberglass rod
Ø 4,5 mm

Click here Video

Click here Productinformation

Application examples:

Almost breakproof

Advantage over fiberglass

Strand + pressing + RUNPOGLIDER

Description Profi-Set see page 2

DATA

ITEM NO.	11120
LENGTH	30 m + 60 m
TOTAL WEIGHT	1,54 kg
DIMENSIONS	H 45 / B 315 / T 395
MATERIAL	triple twisted special plastic tape
Ø ROD	5,3 mm
BENDING RADIUS	15 mm
TOTAL BREAKING LOAD	270 kg
TUBE DIAMETER	for pipe dimensions 16 mm - 40 mm
EAN-Code	9120045473353

ADVANTAGES

- ✓ 50% less frictional resistance
- ✓ 270 kg Total breaking load
- ✓ Virtually break-free even with the tightest radii
- ✓ Advantages compared to glass fibre rod
no buckling, sticking => time savings
- ✓ Guide tip (RUNPOGLEITER) with integrated twist compensation
- ✓ 2 RUNPOGLEITER with twist compensation at the start and end of the spiral

DESCRIPTION

The RUNPO5 is another innovation by RUNPOTEC and a genuine "all-rounder". The patented viewfinder tip, the RUNPOGLEITER with twist compensation allows even the tightest radii to be overcome, with a total breaking load of an incredible 270 kg in relation to the entire pulling system. The special plastic strap with a diameter of 5.3 mm and a triple twist has an even better shearing effect than the 3 mm glass fibre rod; the frictional resistance is only half the normal value due to spot contact. Labour- and time-consuming repair work is no longer necessary, as this cable pulling system is virtually breakage-free. The RUNPO5 can be stored in a very practical box in lengths of 20 m and 30 m. The 40 m RUNPO5 strap cannot be stored in the box.

Optimal field of application: for pipe dimensions 16 mm - 40 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: RUNPO5 in plastic box - all RUNPO 5s are delivered from the factory with 2 x RUNPOGLEITER with twist compensation at the beginning and end of the spiral.

INFORMATION

Compatible accessories:

RUNPO5 Strap

- 20 m | 20240
- 30 m | 20241
- 40 m | 20242



Click here Productinformation

RUNPO Z

- Ø 4 - 6 mm - 20272
- Ø 6 - 9 mm - 20273
- Ø 9 - 15 mm - 20274



Click here Productinformation

DATA SHEET

FIBERGLASS ROAD Ø 4,5 MM PROFI-SET

with steel cage incl. new double run-out system

Item no.: 10052 | 10055 | 10057 | 10047 | 10050



VIDEO
Fiberglass rod Ø 4,5 mm
[Click here Video](#)

[Click here Productinformation](#)

INCL. ACCESSORIES

Achtung! Stromleitend
Attention! electric conductive

Detailed image

BEGINNING

RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA					
ITEM NO.	10052	10055	10057	10047	10050
LENGTH	30 m	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	4,365	4,585	4,805	5,025	5,480
DIMENSION	H 500 / B 380 / T 250				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	for tube diameter 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				

- ADVANTAGES**
- ✓ incl. steel reel
 - ✓ Double run-out system (automatic run-out brake and fast run-out)
 - ✓ Additional parking brake
 - ✓ Glass fibre rod total breaking load up to 1300 kg
 - ✓ Total breaking load 220 kg
Bending radius 120 mm

Rec. tube diamter, bending radius and total breaking load for the fiberglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

DESCRIPTION

Professional set fiberglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

Optimal field of application: for pipe diameters 30 mm - 80 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece fiberglass rod Ø 4.5 mm Profi Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the rod tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve, 1 x connecting sleeve, 1 x shackle, 1 x special adhesive, 1 x roller

INFORMATION

Compatible with:
RUNPOCAM RC2
Length: 10 m | 30 m | 50 m
Item no. 10139 | 10140 | 10141

[Click here Productinformation](#)