

DATA SHEET

FLEXIBLE CAMERA PROBE Ø 3,9 MM

1 Meter for RUNPOCAM RC 2

Item no.: 20488



DATA

ITEM NO.	20488
WEIGHT KG	0,047 kg
DIMENSION	L 340 mm B 270 mm H 85 mm
CAMERA PROBE	100.000 Pixel (320x240)
ILLUMINATION	2 x LED (dimnable)
PROTECTION CLASS	IP 67
FIELD OF VIEW	54 °
DIAMETER	3,9 mm
EAN-CODE	9120045474961

VORTEILE

- ✓ Pipe inspection from Ø 4 mm
- ✓ Protection class IP67
- ✓ Suitable for RUNPOCAM RC 2
- ✓ Angle of view 54°

DESCRIPTION

Camera attachment bendable Ø 4 mm for RUNPOCAM super slim
Application: optimal for short distances with flexible gooseneck. For cavity wall, plant, machinery, engine, ventilation, control or inspection. Hidden cavities, narrow angles, shafts, channels, small lead-throughs and many other possible applications.

Technical data: length: 1 m

Camera head: Ø 3.9 mm, resolution - 100,000 pixels (320 x 240), protection class - IP67, angle of view - 54 degrees, 2 x LED adjustable in 6 steps, auto focus.

Application video: a short, very informative application video can be viewed by scanning the QR code (top left) or on www.runpotec.com.

Scope of delivery: camera head Ø 3.9 mm flexible - 1 metre for RUNPOCAM RC 2

INFORMATION

User with:

RUNPOCAM RC2

Length: 10 m | 30 m | 50 m
Item no.: 10139 | 10140 | 10141

