

GF3 SLIM Fiberglass rod \varnothing 3 mm - incl. digital meter counter

Cable pulling system for pipe innerdiameter 5 – 40 mm

Item no.: 10207 | 10208 | 10209



VIDEO

GF3 SLIM

Click here Video

Automatic
Glide back protection

Integrated digital
meter counter – m/ft

RG4.5 - Guiding head with
Frontthread RTG \varnothing 3 mm
incl. swivel

Ending: Endind joint with
RTG \varnothing 3 mm, stainless steel

Attention!
Electrical
conductive


FTTH
FIBER TO THE HOME

SLIM
 \varnothing 4.5 mm

Rod	Rec. pipe \varnothing	Bending radius	Bending radius rod	Breaking load	Total breaking load
\varnothing					
3 mm	5 – 50 mm	40 mm	28 mm	450 kg	100 kg

FTTH - Glass fiber installation

Speedpipe from \varnothing 5 mm
inner diameter



Optimally suited for occupied pipes

RG4.5 Guiding head \varnothing 4.5 mm



Easy service opening/ Accessory box



Just open one screw

Accessory box 14-parts

Content Accessorybox (14-parts)



DATA

ITEM NO.	10207	10208	10209
LENGTH	20 m	30 m	50 m
WEIGHT	1,22 kg	1,32 kg	1,52 kg
DIMENSION	L 285 mm x W 245 mm x H 65 mm		
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	40 mm		
PIPE INNER \varnothing	optimal from 5 mm - 40 mm		
EAN-CODE	9120045477511	9120045477528	9120045477535

DESCRIPTION

The GF3 SLIM - Fiberglass rod \varnothing 3 mm is a cable pulling tool including a digital meter counter. With a maximum diameter of just \varnothing 4.5 mm, it is ideal for retrofitting occupied pipes or laying fiber optic cables (FTTH - Fiber To The Home). The fiberglass rod \varnothing 3 mm is stored in an extremely shock-resistant plastic box. With the newly developed RG4.5 guide head with front thread RTG \varnothing 3 mm including swivel, it is possible to overcome bending radii up to $R = 40$ mm. The automatic glide back protection prevents the fiberglass rod from accidentally slipping back into the box. The box can be opened for service work with just one screw on the back. The accessory box contains a 14-piece accessory set. The total breaking load of 100 kg refers to the glass fiber rod \varnothing 3 mm including RG4.5 guide head with twist compensation.

Optimal field of application: for pipes with an inner diameter of \varnothing 5 mm - 40 mm.

Application film: you can watch a short, very informative application film by scanning the QR code or on www.runpotec.com

Scope of supply: 1 x GF3 SLIM incl. meter counter in plastic box, 1 x RG4.5 - Guiding head with swivel, contents of the accessory box: 1 x pulling grip, 1 x special adhesive 3 g, 5 x end joint with thread RTG \varnothing 3 mm, 2 x mounting wrench, 2 x pulling eyelet \varnothing 4.5 mm, 1 x starting head \varnothing 6 mm, 1 x starting head \varnothing 4.5 mm, 1 x coupling joint \varnothing 4.5 mm, 1 x adapter thread, 1 x CR2032 button battery

ADVANTAGES

- Super thin pulling system
- Incl. digital meter counter
- RG4.5 guiding head with front thread RTG \varnothing 3 mm incl. swivel
- Automatic glide-back protection
- 14-pieces accessory box
- Total breaking load 100 kg
- Extremely shock-resistant box
- Suitable for occupied pipes or fiber optical cable laying (FTTH)

INFORMATION

Compatibel with (only with adatper thread)

RC2 Inspection camera

- 10 m - Item no.: 10139
- 30 m - Item no.: 10140
- 50 m - Item no.: 10141



Click here
Productinformation