

**GF3 SLIM** Fiberglass rod  $\varnothing$  3 mm – without meter counter

Cable pulling system for pipe innerdiameter 5 – 40 mm

Item no.: 10210 | 10211 | 10212



FTTH - Glass fiber installation



Optimally suited for occupied pipes



Easy service opening/ Accessory box



Rod	Rec. pipe $\varnothing$	Bending radius	Bending radius rod	Breaking load	Total breaking load
$\varnothing$ 3 mm	5 – 50 mm	40 mm	28 mm	450 kg	100 kg

Content Accessorybox (14-parts)



DATA			
ITEM NO.	10210	10211	10212
LENGTH	20 m	30 m	50 m
WEIGHT	1,20 kg	1,30 kg	1,50 kg
DIMENSION	L 285 mm x W 242 mm x H 65 mm		
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	40 mm		
PIPE INNER $\varnothing$	optimal from 5 mm - 40 mm		
EAN-CODE	9120045477542	9120045477559	9120045477566

**DESCRIPTION**

The GF3 SLIM - Fiberglass rod  $\varnothing$  3 mm is a cable pulling tool without meter counter. With a maximum diameter of just  $\varnothing$  4.5 mm, it is ideal for retrofitting occupied pipes or laying fiber optic cables (FTTH - Fiber To The Home). The fiberglass rod  $\varnothing$  3 mm is stored in an extremely shock-resistant plastic box. With the newly developed RG4.5 guiding head with front thread RTG  $\varnothing$  3 mm including swivel, it is possible to overcome bending radii up to  $R = 40$  mm. The automatic glide back protection prevents the fiberglass rod from accidentally slipping back into the box. The box can be opened for service work with just one screw on the back. The accessory box contains a 14-piece accessory set. The total breaking load of 100 kg refers to the glass fiber rod  $\varnothing$  3 mm including RG4.5 guiding head with swivel.

**Optimal field of application:** for pipes with inner diameter of  $\varnothing$  5 mm - 40 mm

**Application film:** you can watch a short, very informative application film by scanning the QR code or on [www.runpotec.com](http://www.runpotec.com)

**Scope of supply:** 1 x GF3 SLIM without meter counter in plastic box, 1 x RG4.5 - Guiding head with swivel, contents of the accessory box: 1 x pulling grip, 1 x special adhesive 3 g, 5 x ending joint with thread RTG  $\varnothing$  3 mm, 2 x mounting wrench, 2 x pulling eyelet  $\varnothing$  4.5 mm, 1 x starting head  $\varnothing$  6 mm, 1 x starting head  $\varnothing$  4.5 mm, 1 x coupling joint  $\varnothing$  4.5 mm, 1 x adapter thread

**ADVANTAGES**

- Super thin pulling system
- RG4.5 - Guiding head with front thread RTG  $\varnothing$  3 mm incl. swivel
- Automatic glide-back protection
- 14-pieces accessory box
- Total breaking load 100 kg
- Extremely shock-resistant box
- Suitable for occupied pipes or fiber optical cable laying (FTTH)

**INFORMATION**

Compatibel with (only with adatper thread)  
**RC2 Inspection camera**  
 10 m - Item no.: 10139  
 30 m - Item no.: 10140  
 50 m - Item no.: 10141



Click here Productinformation