

# DATASHEET

## RUNPOCAM RC2 30 M + PROFI SET - 50 M FOR PIPE INSPECTION FOR LONG DISTANCES UP TO 50 M



Item no.: 11140



CAMERA WITH REEL + MONITOR + CASE + INCLUDED ACCESSORIES:



- A. RG7 RUNPOGLIDER with front thread
- B. Micro memory card 8 GB / adapter
- C. Connection thread set (blind cap, inside and outside connection thread)
- D. SYSTEMGLIDER RC2
- E. Fishing hook
- F. Magnet fishing-set
- G. High-performance 320-lumen rechargeable LED lamp (protection rating IP 67)
- H. Flexible attachment 12 cm
- I. USB / USB-C charging cable 1,5 m
- J. Thread attachment RC2
- K. USB charging adapter 230 V

DATA	Recommended trade price in EURO / excluding VAT
ITEM NO.	11140
CABLE LENGTH m	50 m
TOTAL WEIGHT KG	2,90 kg
CASE SIZE MM	B 395 mm   L 434 mm   H 135 mm
MONITOR	3.5" TFT LCD Monitor 16 M color
CAMERA PROBE	307.200 Pixel (640 x 480)
ILLUMINATION	6 x LED (integrated in camera probe)
PROTECTION CLASS	IP 67 (camera probe and cable)
FIELD OF VIEW	64 °
FOCUSSING DISTANCE	30 mm – 80 mm
POWER SUPPLY	230 V or battery-operated (battery included)
LANGUAGES	DE, EN, FR, ES, PT, IT, NL, DA, SE, NO, FI, PL, CS, HU, RU, IS, LT, SK, SLO, HR, TR
EAN-CODE	9120045476392

### ADVANTAGES

- ✓ Protection class IP67
- ✓ Pipe inspection from Ø 14 mm (inside)
- ✓ Ventilation pipes, drainage pipes, sewage pipes and much more
- ✓ Also for cavity inspection and suspended ceilings
- ✓ Lengths 10 m, 30 m or 50 m
- ✓ Memory function/documentated evidence
- ✓ Photo (JPG), Video (AVI), Audio
- ✓ Spool with camera cable can be easily unwound or rewound via the X BOARD series

### DESCRIPTION

RC2 inspection camera with cable lengths of 10 m, 30 m and 50 m with coil incl. monitor bracket. In W-Boxx system case - compatible with Sortimo. Extra large 3.5" TFT LCD 16 m colour display, protection class IP67 (camera probe and cable), battery operation up to 6 hours. Evidence preservation/storage function: photo, video and audio. CAMERA HEAD with 6 integrated LEDs, enclosed in robust stainless steel head (Ø 13 mm) with RTG Ø 6 mm internal thread. Compatible to all RUNPOTEC products with RTG Ø 6 mm thread (GF3, RUNPOSTICKS, RP 1, glass fibre rod Ø 4.5 - 6 - 7.5 - 9 - 11 - 15 mm).

**Optimal field of application:** For pipe inspections over long distances of up to 50 m. As of 14 mm inner diameter (corresponds to empty pipe Ø 20 mm), but also for larger pipe cross-sections (ventilation systems, drainage systems, sewage pipes etc.). In combination with the RUNPOSTICKS, excellent for cavity wall inspections, suspended ceilings (above high ceiling profiles), manhole and underfloor ducts, maintenance and system inspections.


**Application video:** a short, very informative application video can be viewed by scanning the QR code or on [www.runpotec.com](http://www.runpotec.com).

**Scope of delivery:** RC2 inspection camera with cable incl. reel in system case and incl. accessories: RG7 RUNPOGLIDER with front thread, system slide, LED-battery high performance 320 lumen lamp, Micro Memory Card 8 GB, magnetic catch set, connecting thread set RTG Ø 6 mm, catch hook, flexible attachment 12 cm, USB cable 1,5 m, USB charging plug 230 V, threaded attachment RC 2


### INFORMATION

#### Combinable plug systems:

RP 1 Length 5 - 30 m  [Click here ProductInformation](#)

GF3 Length 20 m | 30m | 50 m  [Click here ProductInformation](#)

Fibreglass rod Ø 4,5/6/7,5/9/11 mm Length 30 up to 300 Meter  [Click here ProductInformation](#)

RUNPOSTICKS Paket: Comfort | Standard  [Click here ProductInformation](#)

# DATA SHEET

## GF4.5 FIBERGLASS ROAD Ø 4,5 MM PROFI-SET

with steel cage incl. new double run-out system

Item no.: 10052 | 10055 | 10057 | 10047 | 10050



**VIDEO**  
Fiberglass rod Ø 4,5 mm  
[Click here Video](#)

[Click here Productinformation](#)

**Achtung!**  
Stromleitend  
**Attention!**  
electric  
conductive

INCL. ACCESSORIES

Detailed image

**BEGINNING**  
RG7 - guiding head with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

**ENDING**  
Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA					
ITEM NO.	10052	10055	10057	10047	10050
LENGTH	30 m	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	4,365	4,585	4,805	5,025	5,480
DIMENSION	H 500 / B 380 / T 250				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	for tube diameter 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				

- ADVANTAGES**
- ✓ incl. steel reel
  - ✓ Double run-out system (automatic run-out brake and fast run-out)
  - ✓ Additional parking brake
  - ✓ Glass fibre rod total breaking load up to 1300 kg
  - ✓ Total breaking load 220 kg  
Bending radius 120 mm

Rec. tube diamter, bending radius and total breaking load for the fiberglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

**DESCRIPTION**

GF4.5 professional set fibreglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (CDP / powder-coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

**Optimal field of application:** for pipe diameters 30 mm - 80 mm.

**Application video:** a short, very informative application video can be viewed by scanning the QR code or on [www.runpotec.com](http://www.runpotec.com).

**Scope of delivery:** 1 x GF4.5 fibreglass rod Ø 4.5 mm Profi Set with steel reel and new double run-out system incl. RG7 RUNPOGLEITER with swivel and front thread at the rod tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve, 1 x connecting sleeve, 1 x shackle, 1 x special adhesive, 1 x roller

**INFORMATION**

**Compatible with:**  
**RC2 Inspectioncamera**  
Length: 10 m | 30 m | 50 m  
Item no. 10139 | 10140 | 10141

[Click here Productinformation](#)